



PIONEER LIME & MINERALS®

Pioneering life...



Pioneer Acrylic Paste Putty

Pioneer Acrylic Paste Putty

PRODUCT DESCRIPTION

PIONEER ACRYLIC PASTE PUTTY is the ready mixed wall putty that gives your walls super smooth finish and which is faster than other ordinary plasters. It is faster to prepare, apply, dry and faster to paint. Being acrylic based it is primer free.

PERFORMANCE FEATURES & BENEFITS

- Superior smoothness and highly even wall finish
- Ready to paint within 48 hours
- Plastic binding makes it more resistant to cracks and flakes
- Special Additives keep it free from deterioration for years
- Can be used for all kinds of surfaces (Sands, Cement, Plaster, Plywood, Gypsum, etc.)
- Also it can be used for new as well as old surfaces
- Self priming putty (Acrylic Base)

RECOMMENDED USAGE

Pioneer Acrylic Putty can be applied on all types of Interior walls, asbestos sheets, concrete etc.

RECOMMENDED APPLICATION

Ensure that the surface to be painted is free from any loose paint, dust, oil or grease. Surface imperfections such as holes and dents are to be filled using a mixture of white cement and fine sand in the ratio of 1:3. Prewet the surface with water before application of 1st (initial) coat of Acrylic Putty

Product	Thinner	Dilution %(by volume)	Application Viscosity (sec)	Recoating** Period (hrs)
Sand the surface with emery paper 180 and wipe clean				
Pioneer Water base Primer Brush, Spray	Water	8-10 15-20	30-40 20-25	6-8 hrs
Pioneer Acrylic Putty Putty Knife	Water	As required	N.A.	4-6 hrs
Sand the surface with emery paper 180 and wipe clean				
Pioneer Water base Primer Brush, Spray	Water	8-10 15-20	30-40 20-25	6-8 hrs
Sand the surface with emery paper 320 and wipe clean				
Pioneer's Lotus Plastic Emulsion 1 Coat Brush, Roller, Spray	Water	40-45 65-70	20-25 20-25	4 hrs
Pioneer's Lotus Plastic Emulsion 2 Coats Brush, Roller, Spray	Water	40-45 65-70	20-25 20-25	4 hrs

**Recoat period is quoted for 28-30°C and 60-65% Relative Humidity; these may vary under different conditions.

Pioneer Acrylic Paste Putty

TECHNICAL DATA

- a) **Coverage**:** 10 - 12 sq.ft./kg/coat
- b) **Pot Life of thinned material:** 1.5 hrs. (Temp. 30 +/- 2°C, %RH 65 +/- 5)
- c) **Dry to Recoat:** 2 - 3 hrs. (Temp. 30 +/- 2°C, %RH 65 +/- 5)
- d) **Shelf – Life:** 1 year from date of manufacture in tightly closed containers away from direct sunlight and excessive heat

**Actual Coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

PRECAUTIONS

- Before application of the material surface should be clean and free from efflorescence/lime blooming
- Do not apply the material without prewetting the surface for the first coat
- Ensure that the material is mixed homogeneously with water and allowed to stand 5-10 minutes before application
- Do not apply the materials to fill the structural cracks
- Though the material is non-toxic, care should be taken to avoid dust inhalation while mixing and handling

POST APPLICATION INSTRUCTION

For the best performance of the topcoat ensure proper washing and cleaning of algal or fungal growth if any at regular intervals.

SAFETY FEATURES

Non - Flammable

PACK SIZES AND SHADE RANGE

Pack size available:
20kg bag

Shade range:
White



CONTACT US

PIONEER LIME & MINERALS

B/14, 1st Floor, Raj Hill, Dattapada Road, Borivali (E), Mumbai 400066
T: 28708586 | e-mail: info@pioneerlm.in | Website: www.pioneerlm.in

