



PIONEER LIME & MINERALS®

Pioneering life...



Pioneer Crack Repair

PRODUCT DESCRIPTION

Crack Repair is highly flexible, asbestos free, high solids filler for major and minor cracks. It is cement based crack filler specially developed to fill cracks. It contains finest grades of cement, sand, selected fillers and best quality polymers to give it unique properties. The materials should be used only to fill shrinkage cracks and other small cracks in plaster. This should not be used to fill structural cracks and construction joints. It is available in powder form.

PERFORMANCE: FEATURES & BENEFITS

- Excellent bonding to the base plaster
- Flexible
- Scratch resistant
- Water resistant
- UV resistant
- Suitable for interiors as well as exteriors

ADVANTAGES AND BENEFITS

ADVANTAGES	BENEFITS
Good workability	Cost effective
Ease of use at site	Saves Time
Consistent work quality	Quick Fix for cracks

SURFACE PREPARATION

- Surface should be dry and clean
- Clean loose particles, dirt, grease and traces of foreign material from the surface, by using sand paper or by chipping
- Cracks must be dry before application begins
- Before application cut a V groove in the crack by using suitable tool

Pioneer Crack Repair

MIXING

- Take clean water in a clean bucket
- Add required quantity of PIONEER CRACK REPAIR and stir continuously to obtain a lump free paste
- Wait for 10 minutes for the additives to dissolve
- Re-mix again for about 2 minutes and the mixture is now ready for use
- Use the mix within 30 minutes

RECOMMENDED APPLICATION

- Take clean water to dampen the opened crack, Allow excess water to drain off
- Use a steel blade/trowel to apply the above mix
- Press the mix firmly to fill the crack completely
- Level and smoothen the surface with a steel trowel
- Use Sand Paper if required

PRECAUTIONS

PIONEER CRACK REPAIR contains only eco-friendly fillers and additives. However, being white cement based it is alkaline and hence it is advisable to avoid direct eye contact and skin contact with this. In case of eye contact, flush with clean water at least for 15 minutes and seek medical help.

SAFETY FEATURES

Non - Flammable

PACKAGING & STORAGE

- PIONEER CRACK REPAIR is supplied in 1kg, 5kg and 20kg bag
- PIONEER CRACK REPAIR has a shelf life of 6 months if stored in a cool and dry location



**As the temperature, humidity, water addition and other parameters vary from site to site; the above information should be treated as a general guidelines.

CONTACT US

PIONEER LIME & MINERALS

B/14, 1st Floor, Raj Hill, Dattapada Road, Borivali (E), Mumbai 400066
T: 28708586 | e-mail: info@pioneerlm.in | Website: www.pioneerlm.in

