

## NATURA IN & OUT TEXTURES

### PRODUCT DESCRIPTION

Pioneer's Natura In & Out Textures are composed of high quality acrylic based co-polymer and are modified to give distinctive appeal. Natura Texture covers wide range of Trowel, Spray, Stone and Roller Coat Textures.

### PERFORMANCE: FEATURES & BENEFITS





- Unique Designer Textures
- Excellent Flexibility & Elasticity
- Works on any Surface
- Breathes Out Trapped Moisture
- Longest/Permanent Shade Life
- Fire Retardant
- Permanent Finishes
- Water Repellent
- Suitable for Interiors/ Exteriors
- Economic & Time Effective
- Weather Proof

### RECOMMENDED USAGE

Pioneer's Natura Textures can be applied on all types of interior and exterior surfaces like sand faced plasters, brick, concrete etc.

### RECOMMENDED APPLICATION

Natura Textures can be applied with spray/roller or stainless steel trowel. It takes 4 hours for surface dry and 24 hours for hard dry. It needs only one coat application if the surface is new and smooth. It does not need any special preparation but if the plaster is very absorbent, old and uneven surface, it should first brushed down and treated with proper coat of sealer.

ITEMS	DESCRIPTION	APPLICATION	USES
Trowel Texture	• Grooved finish • Pure Acrylic emulsion based • Formulated to withstand humidity, rain and variable climates • Can be over coated with top coat of acrylic paint.	 Trowel Brush Spray	For Interior and Exterior
Spray Texture	• Spray finish • Pure Acrylic emulsion based • Formulated to withstand humidity, rain and variable climates • Can be over coated with top coat of acrylic paint.	 Spray	For Interior and Exterior
Stone Texture	• Stone finish • Pure Acrylic emulsion based • Formulated to withstand humidity, rain and variable climates • Can be over coated with clear Lacquer as an optional top coat.	 Trowel Spray	For Interior and Exterior
Roller Coat Texture	• Subtle Acrylic emulsion based texture • Formulated to give different roller pattern with fine medium and bold texture effect.	 Brush Roller	For Interior and Exterior

## TECHNICAL DATA

- a) **Coverage\*\*:** 2.5 - 3 sq.ft./kg
- b) **Pot Life of thinned material:** 1.5 hrs. (Temp. 30 +/- 2°C, %RH 65 +/- 5)
- c) **Dry to Recoat:** 16 - 18 hrs. (Temp. 30 +/- 2°C, %RH 65 +/- 5)
- d) **Shelf – Life:** 3 months from date of manufacture in tightly closed containers away from direct sunlight and excessive heat

\*\*Actual Coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

## PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application
- Use of Stainers or colorants is not recommended
- Thinning is not advisable
- Do not keep the material open for long time
- Product cannot be applied on surface/substrates that are subjected to continuous seepage or dampness
- Stir well before use

## POST APPLICATION INSTRUCTION

For the best performance of the paint, ensure proper washing and cleaning of algal or fungal growth if any at regular intervals.

## SAFETY FEATURES

Non - Flammable

## PACK SIZES AND SHADE RANGE

### Pack size available:

5kg and 25kg bag

### Shade range:

White/Off White/Base



(Top coat of Pioneer's Safari Exterior Emulsion or Lotus Plastic Emulsion)

## CONTACT US

### PIONEER LIME & MINERALS

B/14, 1st Floor, Raj Hill, Dattapada Road, Borivali (E), Mumbai 400066  
T: 28708586 | e-mail: info@pioneerlm.in | Website: www.pioneerlm.in

