



PIONEER LIME & MINERALS[®]

Pioneering life...



Safari Acrylic Exterior Emulsion

PRODUCT DESCRIPTION

PIONEER'S Safari Exterior Emulsion is water - based exterior wall finish suitable for dry to moderately humid climatic conditions.

PERFORMANCE FEATURES & BENEFITS

Safari Exterior Emulsion offers excellent resistance to chalking, cracking and weathering in comparison to Cement paints. Safari Exterior Emulsion gives cleaner shades which do not fade and last longer. Safari Exterior Emulsion offers good anti-algal performance in dry to moderately humid climatic conditions.

RECOMMENDED USAGE

Safari Exterior Emulsion is an exterior wall finish that can be applied on all types of exterior cement plasters, asbestos sheets, concrete, etc. Product cannot be applied on roof tiles and on surfaces that are subjected to continuous seepage and dampness.

RECOMMENDED APPLICATION

Ensure that the surface to be painted is free from any loose paint, dust or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly and cleaned with water. Surface imperfections such as holes, dents, fine cracks are to be filled using Pioneer Wall Putty or a mixture of white cement and fine sand (in the ratio of 1:3).

Product	Thinner	Dilution %(by volume)	Application Viscosity (sec)	Recoating** Period (hrs)
Pioneer Cement Putty	Water	As per requirement to form paste	Paste form	4 hrs
Safari Water base Primer	Water	90-110 40-45	15-18 33	4 hrs
Safari Exterior Emulsion Brush, Roller, Spray	Water	max 75 max 75	20-25 20-25	4-6 hrs
Safari 100% Exterior Emulsion Brush, Roller, Spray	Water	max 75 max 75	20-25 20-25	4-6 hrs

**Recoat period is quoted for 25°C and 50% Relative Humidity; these may vary under different conditions.

Safari Acrylic Exterior Emulsion

Safari Acrylic Exterior Emulsion

TECHNICAL DATA

- a) **Coverage**:** On normal masonry surface by brushing: 100 – 110 sq.ft/coat
- b) **Drying Time:** Surface Dry time – 30 minutes
- c) **Gloss Level/Sheen Level:** 1 – 6 at 60 deg GH
- d) **Flash Point (IS 101/1987, Part 1, Sec 6):** NA
- e) **Stability of Thinned Paint:** Use within 24 hrs
- f) **Shelf – Life:** 1 year from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

**Actual Coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.

PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application
- Do not over thin or over extend the brush
- Ensure that horizontal surfaces like top of window, ledges, etc. are painted with 3 coats for greater protection
- Tinted paints need through shaking immediately after tinter addition as well as before use
- Stir well and strain before use
- Excessive bird droppings/spitting may affect the performance of the product

POST APPLICATION INSTRUCTION

For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth at regular intervals.

SAFETY FEATURES

Non - Flammable

PACK SIZES AND SHADE RANGE

Pack size available:

1ltr, 4ltr, 10ltr and 20ltr bucket

Shade range:

Currently available in white and various light shades



CONTACT US

PIONEER LIME & MINERALS

B/14, 1st Floor, Raj Hill, Dattapada Road, Borivali (E), Mumbai 400066

T: 28708586 | e-mail: info@pioneerlm.in | Website: www.pioneerlm.in

