



PIONEER LIME & MINERALS®

Pioneering life...



Pioneer Tile Adhesive (TA)

PRODUCT DESCRIPTION

PIONEER'S TA is a ceramic tile adhesive. It is a pre-packed cementitious tile adhesive which ensures an excellent bond on concrete, plastered and even ceramic and mosaic tile surfaces. Pioneer TA ensures perfect water tightness.

PERFORMANCE: FEATURES & BENEFITS

- Excellent adhesion, low shrinkage
- Suitable for indoor and outdoor floor tile on tile application
- Sufficiently flexible to accommodate physical & thermal movements
- Needs no curing, need no hacking, or mechanical key on the surfaces

ADVANTAGES AND BENEFITS

ADVANTAGES	BENEFITS
Pre-packed factory controlled & ensures consistent quality	Cost effective
Excellent adhesion hence can be used on tile	Saves Time
Excellent water proofing characteristics	Quick Fix
Can also be used for fixing of acoustic and insulating boards	Good Durability

SURFACE PREPARATION

- Surface should be dry and clean
- All loose particles of mortar and paints must be physically removed
- All traces of grease or oil must be removed with de-greaser
- It can be applied directly on concrete, cements, lime mortars and existing tiles

MIXING

- Pioneer TA should be mixed with water in the ratio of 3:1 by volume
- A slow speed drill fitted with a suitable mixing paddle is recommended
- Hand mixing may be allowed drill/paddle is not available
- Remove excess adhesive with a damp cloth before material has set

RECOMMENDED APPLICATION

- Take clean water to dampen the opened crack, Allow excess water to drain off
- Use a steel blade/trowel to apply the above mix
- Press the mix firmly to fill the crack completely
- Level and smoothen the surface with a steel trowel
- Use Sand Paper if required

PRECAUTIONS

PIONEER TA is non toxic. However, splashes on the skin and contact with eyes, should be washed well with water and seek medical advice.

SAFETY FEATURES

Non - Flammable

PACKAGING & STORAGE

- PIONEER TA is supplied in 5kg and 20kg bag
- PIONEER TA is to be stored in a cool and dry location

***As the temperature, humidity, water addition and other parameters vary from site to site; the above information should be treated as a general guideline.



CONTACT US

PIONEER LIME & MINERALS

B/14, 1st Floor, Raj Hill, Dattapada Road, Borivali (E), Mumbai 400066
T: 28708586 | e-mail: info@pioneerlm.in | Website: www.pioneerlm.in

